

SAFETY DATA SHEET

1. Identification

Product identifier	SDAG-13, Anhydrous
Other means of identification	
Synonyms	Ethanol denatured with ethyl acetate, Specially denatured alcohol
Recommended use	General purpose solvent.
Recommended restrictions	Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in the US, etc.
Manufacturer/Importer/Supplie	r/Distributor information
	Greenfield Global Inc

Company name	Greenfield Global Inc.
Address	6985 Financial Drive
	Missisauga, Ontario L5N 0G3
	Canada
Telephone	(905) 790-7500
Website	http://www.greenfield.com
Emergency phone number	CANUTEC: (613) 996-6666

2. Hazard identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2
Label elements		
	$\wedge \wedge$	
	$\sim \sim$	
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapour. Causes s	serious eye irritation.
Precautionary statement		
Prevention	Keep container tightly closed. Ground and bo explosion-proof electrical/ventilating/lighting e	pen flames and other ignition sources. No smoking. nd container and receiving equipment. Use quipment. Use non-sparking tools. Take action to fter handling. Wear protective gloves/protective
Response	EYES: Rinse cautiously with water for several	contaminated clothing. Rinse skin with water. IF IN I minutes. Remove contact lenses, if present and ersists: Get medical advice/attention. In case of fire: emical powder, carbon dioxide to extinguish.
Storage	Store in a well-ventilated place. Keep cool.	
Disposal	Dispose of contents/container in accordance	with local/regional/national/international regulations.
Supplemental information	None.	
Other hazards	None known.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	98.39
Ethyl acetate	Acetic acid ethyl ester	141-78-6	1.12
Other components below r	eportable levels		0.49

SDAG-13, Anhydrous

1 First-aid measures	
4. First-aid measures	News to feach size Oolling should be a feacher of a second state
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with wate immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can a so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapour.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate a ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For person protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

US. ACGIH Threshold Limit Valu Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Ethyl acetate (CAS 141-78-6)	TWA	400 ppm
	ional Health & Safety Code, Sche	edule 1, Table 2)
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Ethyl acetate (CAS 141-78-6)	TWA	1440 mg/m3
		400 ppm
Canada. British Columbia OELs. Safety Regulation 296/97, as amo		for Chemical Substances, Occupational Health and
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Ethyl acetate (CAS 141-78-6)	TWA	150 ppm
	STEL	1000 ppm
Ethyl acetate (CAS 141-78-6)	TWA	400 ppm
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control	-	400 ppm
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components	TWA of Exposure to Biological or Che	400 ppm emical Agents)
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS	TWA of Exposure to Biological or Che Type	400 ppm emical Agents) Value
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry	TWA of Exposure to Biological or Che Type STEL TWA	400 ppm emical Agents) Value 1000 ppm
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components	TWA of Exposure to Biological or Che Type STEL TWA v of Labor - Regulation respecting	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety)
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components	TWA of Exposure to Biological or Che Type STEL TWA v of Labor - Regulation respecting Type	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS	TWA of Exposure to Biological or Che Type STEL TWA v of Labor - Regulation respecting Type	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS	TWA of Exposure to Biological or Che Type STEL TWA of Labor - Regulation respecting Type TWA	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3 1000 ppm
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Saskatchewan OELs (O	TWA of Exposure to Biological or Che Type STEL TWA v of Labor - Regulation respecting Type TWA TWA	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3 1000 ppm 1440 mg/m3 400 ppm egulations, 1996, Table 21)
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Saskatchewan OELs (O Components	TWA of Exposure to Biological or Che Type STEL TWA of Labor - Regulation respecting Type TWA TWA TWA	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3 1000 ppm 1440 mg/m3 400 ppm egulations, 1996, Table 21) Value
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Saskatchewan OELs (O Components	TWA of Exposure to Biological or Che Type STEL TWA of Labor - Regulation respecting Type TWA TWA TWA TWA TWA 15 minute	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3 1000 ppm 1440 mg/m3 400 ppm egulations, 1996, Table 21) Value 1250 ppm
Ethyl acetate (CAS 141-78-6) Canada. Ontario OELs. (Control Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Saskatchewan OELs (O Components Ethanol (CAS 64-17-5)	TWA of Exposure to Biological or Che Type STEL TWA of Labor - Regulation respecting Type TWA TWA TWA TWA TWA TWA TWA Stream of the stream of t	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3 1000 ppm 1440 mg/m3 400 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm
Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6) Canada. Quebec OELs. (Ministry Components Ethanol (CAS 64-17-5) Ethyl acetate (CAS 141-78-6)	TWA of Exposure to Biological or Che Type STEL TWA of Labor - Regulation respecting Type TWA TWA TWA TWA TWA 15 minute	400 ppm emical Agents) Value 1000 ppm 400 ppm g occupational health and safety) Value 1880 mg/m3 1000 ppm 1440 mg/m3 400 ppm egulations, 1996, Table 21) Value 1250 ppm

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures	, such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Colourless.
Odour	Ester odor.
Odour threshold	Not available.
рН	Not applicable.
Melting point/freezing point	-100 °C (-148 °F) (Approximate)
Initial boiling point and boiling range	72 - 79 °C (161.6 - 174.2 °F) (Approximate)
Flash point	12 °C (53.6 °F) Tag closed cup (ASTM D-56)
Evaporation rate	1.8 (Butyl acetate = 1)
Flammability (solid, gas)	Not applicable.
Vapour pressure	Not available.
Vapour density	1.6 (Air=1)
Relative density	0.794 (20 °C (68 °F))
Solubility(ies)	
Solubility (water)	Complete
Partition coefficient (n-octanol/water)	0.032 (Approximate)
Auto-ignition temperature	422 °C (791.6 °F) (Approximate)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Dynamic viscosity	1.35 cP (20 °C (68 °F))
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Percent volatile	100
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, sto

Reactivity	I he product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on toxicological effects

Acute toxicity

Species	Test Results
opecies	1621 1620112
Rat	117 - 125 mg/l, 4 Hours
	117 120 mg/l, 4 hours
Rat	10470 mg/kg
Nat	10+10 mg/kg
Rabbit	> 18000 mg/kg
Rabbit	> 10000 mg/kg
Rat	58.6 mg/l, 4 hours
	56.0 mg/l, 4 hours
Pat	10170 mg/kg
	ause temporary irritation.
Causes serious eye irritation.	
n	
ant	
78-6)	Irritant
Not a respiratory sensitiser.	
This product is not expected to	o cause skin sensitisation.
No data available to indicate product or any components present at greater than 0.1% are	
	A3 Confirmed animal carcinogen with unknown relevance to humans.
arcinogenicity	
	Confirmed animal carcinogen with unknown relevance to humans
Possible reproductive hazard.	
Not classified.	
	This product is not expected to No data available to indicate p mutagenic or genotoxic. arcinogenicity Possible reproductive hazard.

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be h

Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Ethanol (CAS 64-17-5)				
Aquatic				
Acute				
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours	
	EC50	Freshwater algae	275 mg/l, 72 hours	
		Marine water algae	1900 mg/l	
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours	
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours	
		Marine water invertebrate	857 mg/l, 48 hours	
Other	EC50	Lemna minor	4432 mg/l, 7 days	
Chronic				
Algae	NOEC	Marine water algae	1580 mg/l	
Fish	NOEC	Freshwater fish	250 mg/l	
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days	
		Marine water invertebrate	79 mg/l, 96 hours	
Other	NOEC	Lemna minor	280 mg/l, 7 days	
Other				
Acute				
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours	
Terrestrial				
Acute				
Plant	EC50	Terrestrial plant	633 mg/kg dw	
sistence and degradability	Expected to b	be readily biodegradable.		
accumulative potential				
Partition coefficient n-octa SDAG-13, Anhydrous	nol / water (log	Kow) 0.032, (Approximat	te)	
bility in soil	Expected to b	Expected to be highly mobile in soil.		
ner adverse effects	The product of potential.	The product contains volatile organic compounds which have a photochemical ozone creation potential.		
. Disposal consideratio	ons			
posal instructions		Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.		
cal disposal regulations	Dispose in ac	ccordance with all applicable regulatio	ns.	
zardous waste code		The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
ste from residues / unused ducts	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
ntaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container i emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.			

14. Transport information

· · · · · · · · · · · · · · · · · · ·	
TDG	
UN number	UN1987
UN proper shipping name	ALCOHOLS, N.O.S. (Ethanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	П
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
ΙΑΤΑ	
UN number	UN1987
UN proper shipping name	Alcohols, n.o.s. (Ethanol; Ethyl acetate)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1987
UN proper shipping name	ALCOHOLS, N.O.S. (Ethanol; Ethyl acetate)
Transport hazard class(es)	
Class	3
Subsidiary risk	
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed. **Greenhouse Gases** Not listed. **Precursor Control Regulations** Not regulated. International regulations **Stockholm Convention** Not applicable. **Rotterdam Convention** Not applicable. **Kyoto Protocol** Not applicable. **Montreal Protocol** Not applicable. **Basel Convention** Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	01-July-2021	
Revision date	-	
Version No.	01	
Disclaimer	This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the action of the terms.	

made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.